

TABLE OF CONTENTS

	Page
ABSTRACT	ix
1 INTRODUCTION	1
1.1 Problem Definition and Objective	1
1.2 Background and previous work	2
1.2.1 Experiments	3
1.2.2 Computational models	5
1.2.2.1 Micromechanical models	7
1.3 Approach and Relevance of the Work	9
2 MULTI-SCALE APPROACH	12
2.1 Background	12
2.2 Continuum/discrete model	13
2.2.1 Finite Element discretization	16
2.2.1.1 Equation of motion	16
2.2.1.2 Direct Time Integration Algorithm	18
2.2.2 Continuum Model: Finite Deformation Continuum Microcrack- ing Model	20
2.3 Discrete model: Contact/Interface Law with Finite Kinematics	23
2.4 Model for ductile materials	26
2.4.1 Large Deformation Plasticity Model	26
2.4.1.1 Equation of State and Artificial Viscosity	27
2.4.2 Thermo-mechanical coupling	28
2.4.3 Adaptive Remeshing	29
2.4.3.1 Refinement /coarsening technique	29
2.4.3.2 Geometrical optimization	31

2.4.3.3	Transfer Operator	34
2.5	Achievements	35
2.5.1	Modified Taylor test	36
2.5.2	Rod-on-rod impact simulation	41
2.5.2.1	Continuum/Discrete vs. Discrete Damage Models	43
2.5.2.2	Effect of Friction Between Fragments	44
2.5.2.3	Effect of Model Type on Fracture Patterns	45
2.5.2.4	Effect of Potential Fragment/Mesh Size	47
2.6	Discussion	49
3	MICROMECHANICAL MODEL	52
3.1	Introduction	52
3.2	Generation of the polycrystalline microstructure	52
3.2.1	Digitalization	52
3.2.2	Voronoi Tessellations	53
3.2.3	Other methods	56
3.3	Computational Model	57
3.3.1	Anisotropic elastic model	58
3.4	Contact/interface algorithm	58
3.4.1	Law1	62
3.4.2	Law11	65
3.4.2.1	Initial slope	66
3.4.2.2	Cohesive law under compression	66
3.4.3	Law111	68
3.4.4	Other cohesive laws	71
3.4.5	Time step calculation	72
3.4.6	Rate and temperature effects	73
3.5	Explicit integration scheme	74
3.6	Initial and boundary conditions	74
3.7	Physically based consideration on the model	76

3.7.1	Weibull distribution	78
3.7.2	Glassy phase, glass pockets and initial defects	81
3.8	Microcrack evolution and stereology	81
4	RESIDUAL THERMAL STRESS ANALYSIS..	85
4.1	Model	85
4.2	Implicit algorithm	87
4.2.1	Boundary Conditions	88
4.3	Analysis of residual thermal stress in ceramics	90
4.3.1	Numerical analysis with simple microstructures	90
4.3.1.1	Study of convergence	91
4.3.1.2	Effect of grain orientation	94
4.3.1.3	Effect of microstructural defects	95
4.3.1.4	*Grain size effect	96
4.3.2	Calculation with complex microstructures	97
4.4	Discussion	100
5	MICROMECHANICAL ANALYSIS OF NORMAL PLATE IMPACT EX- PERIMENTS	103
5.1	Introduction	103
5.2	Experiments	103
5.3	Computational modeling	107
5.3.1	Boundary Conditions	109
5.4	Solution convergence	112
5.5	A parametric study	119
5.5.1	Effect of the RVE size	120
5.5.2	Effect of K_{IC} and T_{max}	121
5.5.2.1	Effect of K_{IC}	122
5.5.2.2	Effect of T_{max}	124
5.5.2.3	Discussion of the effect of K_{IC} and T_{max}	124
5.5.2.4	Combination of K_{IC} and T_{max}	126

5.5.3	Effect of initial defects	1-26
5.5.4	Effect of a Weibull distribution	127
5.5.4.1	Variation on T_{max}	127
5.5.5	Rate dependent models	130
5.5.6	Discussion	134
5.6	Simulations with realistic values of T_{max}	136
5.6.1	Parametric study	137
5.6.2	An study of the crack propagation and branching	138
5.6.3	Residual thermal stresses	146
5.7	Analysis of the normal plate impact experiments	146
5.7.1	shot 88-04	149
5.7.1.1	Simulations with more realistic microstructures	152
5.7.2	Shot 89-03.	155
5.7.3	Shot 92-09	159
5.7.4	Shot 92-11	162
5.7.5	Damage in compression	165
5.8	Concluding remarks	173
6	PRESSURE-SHEAR EXPERIMENTS	174
6.1	Introduction	174
6.2	Numerical Simulations with an RVE subjected to multiaxial load	175
6.2.1	Boundary and Initial conditions:	175
6.2.2	Microcrack evolution and material pulverization	178
6.2.3	Effect of representative volume element (RVE) size	180
6.2.4	Effect of T_{max} and K_{IC}	180
6.2.5	Effect of loading conditions	185
6.2.6	Effect of initial defects	185
6.2.7	Effect of grain elastic anisotropy	185
6.2.7.1	Effect of considering the ceramic to be transversely isotropic	189

6.2.8	Effect of grain size	189
6.2.9	Weibull distribution of interface parameters	189
6.2.10	Effect of grain morphology	192
6.3	Analysis including surface roughness and frictional sliding.	196
6.3.1	Boundary conditions	197
6.3.2	Periodicity in contact	198
6.3.3	Surface Roughness	200
6.3.4	Analysis of the sliding friction between the specimen and target	201
6.3.4.1	Study of convergence	206
6.3.4.2	Effect of surface roughness	209
6.3.4.3	Effect of the material properties of the steel target .	212
6.3.4.3.1	Effect of the initial yield stress	212
6.3.4.3.2	Effect of the hardening exponent	213
6.3.4.4	Effect of interfacial strength in the ceramic.	214
6.3.4.5	Effect of the initial velocity and angle	215
6.4	Full scale simulation	219
6.4.0.6	Determination of the gap between the flyer and specimen	219
6.4.1	Results.	220
6.5	Conclusions	220
7	SUMMARY	227
	LIST OF REFERENCES	229
	APPENDIX.	238
A.1	Procedure to determine the initial slope of the cohesive laws	238
A.2	Study of stability for linear and quadratic interface elements	240
A.3	Analysis of the size and shape of interface and continuum elements .	242
A.4	Discussion	245
VITA	247